LCD Monitor User Manual

The color and the appearance may differ depending on the product, and the specifications are subject to change without prior notice to improve the performance.

Table Of Contents

MAJO	R SAFETY PRECAUTIONS	
В	efore You Start	1-1
С	ustody and Maintenance	1-2
S	afety Precautions	1-3
INSTA	ALLING THE PRODUCT	
P	ackage Contents	2-1
In	stalling the Stand	2-2
R	emoving the Stand	2-3
C	onnecting with a PC	2-4
K	ensington Lock	2-5
USING	THE PRODUCT	
S	etting the Optimal Resolution	3-1
St	tandard Signal Mode Table	3-2
In	stalling the Device Driver	3-3
P	roduct Operating Buttons	3-4
U	sing the Screen Adjustment Menu (OSD: On Screen Display) 3	3-5
INSTA	ALLING THE SOFTWARE	
N	atural Color	4-1
M	agicTune	4-2
M	ultiScreen	4-3
TROU	BLESHOOTING	
М	onitor Self-Diagnosis {	5-1
	efore Requesting Service	
F	AQ	5-3
MORE	INFORMATION	
S	pecifications	6-1
P	ower Saving Function 6	6-2
C	ontact SAMSUNG WORLDWIDE	6-3
C	orrect Disposal of This Product (Waste Electrical & Electronic Equipment) - Europe only 6	6-4

1 Major Safety Precautions

1-1 Before You Start

Icons used in this manual

ICON	NAME	MEANING
1	Caution	Indicates cases where the function may not work or the setting may be canceled.
	Note	Indicates a hint or tip to operate a function.

Using this Manual

- Make yourself fully aware of the safety precautions before using this product.
- · If a problem occurs, refer to the 'Troubleshooting' section.

Copyright Notice

The contents of this manual are subject to change without prior notice for performance improvement.

Copyright © 2010 Samsung Electronics Co., Ltd. All Rights Reserved.

The copyright of this manual is reserved by Samsung Electronics, Co., Ltd.

The contents of this manual may not be partially or in whole reproduced, distributed or used in any form without the written permission of Samsung Electronics, Co., Ltd.

The SAMSUNG logo and SyncMaster are the registered trademarks of Samsung Electronics, Co., Ltd.

Microsoft, Windows and Windows NT are the registered trademarks of Microsoft Corporation.

VESA, DPM and DDC are the registered trademarks of the Video Electronics Standard Association.

The ENERGY STAR® logo is the registered trademark of the U.S. Environmental Protection Agency.

All other trademarks mentioned herein belong to their respective companies.

Major Safety Precautions 1-1


1-2 Custody and Maintenance

External Surface and Screen Maintenance

Clean the product with a soft dry cloth.

- Do not clean the product with an inflammable substance such as benzene or thinner or with a wet cloth. This may result in a problem with the product.
- Do not scratch the screen with your fingernails or a sharp object.
 - This may result in scratches or damage to the product.
- Do not clean the product directly by spraying water onto the product.
 - If water enters the product, it may result in fire, electric shock or a problem with the product.
- A white stain may be generated on the surface of the highglossy model due to the inherent characteristics of the material, if a supersonic humidifier is used.






Securing the Installation Space

- Keep the required distances between the product and other objects (e.g. walls) to ensure proper ventilation.
 Failing to do so may result in fire or a problem with the product due to an increase in the internal temperature.
 Install the product so the required distances shown in the figure are kept.
 - The appearance may differ depending on the product.

When installing the product with a stand



About persistent images

- Displaying a still image for a long time may create a persistent image or stain on the screen. If you do not use the product for a long time, set the power-saving mode or screen saver.
- Due to technological constraints of the LCD Panel manufacturer, the images generated by this product may appear either brighter or darker than normal by appr. 1ppm (parts per million) pixel.
 - The number of sub-pixels of an LCD panel by size: The number of Sub-Pixels = Max. Horizontal Resolution x Max. Vertical Resolution x 3

Example) If the maximum resolution is 1920×1080 , the number of sub-pixels is $1920 \times 1080 \times 3 = 6,220,800$.

1-2 Major Safety Precautions

Icons used for safety precautions

ICON	NAME	MEANING
<u>^</u>	Warning	Failing to follow the precautions marked with this sign, may result in a serious injury or even a fatality.
<u>^</u>	Caution	Failing to follow the precautions marked with this sign, may result in a personal injury or property damage.

Meaning of Signs



Do not perform.



Must be followed.



Do not disassemble.



The power plug must be unplugged from the wall outlet.



Do not touch.



Must be grounded to prevent electric shock.

Power Related

The product image used in the following pictures for your reference may look different from the actual product.



🚺 Warning



Avoid using a damaged power cord or plug or a loose power outlet.

Otherwise, it may result in electric shock or



Avoid connecting multiple electric appliances to a single wall outlet.

Otherwise, it may result in fire due to overheating of the wall outlet.

Otherwise, it may result in fire.



Avoid plugging in or unplugging the power supply with wet hands.

Otherwise, it may result in electric shock.



Plug the power plug in firmly.



Make sure to connect the power cord to a grounded wall outlet (for insulation class 1 equipment only).

Otherwise, it may result in electric shock or



Avoid bending or twisting the power cord



Keep the power cord and the product away from a heater.

Otherwise, it may result in electric shock or



excessively and avoid placing heavy objects on the cord.

Otherwise, it may result in electric shock or fire due to a damaged power cord.

1-3

If the pins of the power plug or the wall outlet are covered in dust, clean it using a dry cloth.

Otherwise, it may result in fire.

Major Safety Precautions

Caution



Avoid unplugging the power plug while the product is operating.

Otherwise, it may damage the product due to electric shock.



Make sure to use only the power cord supplied by our company. In addition, do not use the power cord of another electric appliance.

Otherwise, it may result in electric shock or



When unplugging the power plug from the wall outlet, make sure to hold it by the plug and not by the cord.

Otherwise, it may result in electric shock or



Connect the power plug to a wall outlet that can be easily reached.

When a problem occurs with the product, you must unplug the power plug to cut the power off completely. You cannot cut the power off completely using only the power button on the product.

Installation Related



Warning



Avoid placing burning candles, mosquitorepellent or cigarettes on the product and installing the product near a heater.

Otherwise, it may result in fire.



Otherwise, it may result in injury.

Ask an installation engineer or relevant company to install the product onto the wall.



Avoid installing the product in a badly-ventilated location such as inside a bookshelf or closet.

Otherwise, it may result in fire due to internal over-heating.



Make sure to use the specified wall mount.

Keep a distance of at least 10 cm from the wall when installing the product for ventilation.

Otherwise, it may result in fire due to

internal over-heating.



Keep the plastic bags used to pack the product away from children.

If children place the plastic bags over their heads, they may suffocate.



Avoid installing the product in a location that is unstable or exposed to excessive vibrations such as on an unstable or slanted shelf.

- The product may fall and this may result in damage to the product or injury.
- If you use the product in a location exposed to excessive vibrations, it may result in a problem with the product or fire.

Avoid installing the product in a location exposed to direct sunlight and installing the



Avoid installing the product in a location exposed to dust, moisture (sauna), oil, smoke or water (rain drops) and installing it within a vehicle.

This may result in electric shock or fire.



heater.

This may shorten the product life cycle or cause fire.

product near a heat source such as a fire or



Avoid installing the product at an easily reachable height where children may reach it.

- If a child touches the product, the product may fall and this may result in injury.
- Since the front part is heavier, install the product on a flat and stable surface.

1-3 Major Safety Precautions

Caution



Do not let the product drop while moving it.

This may result in a problem with the product or injury.




Do not place the product face down on the floor.


This may damage the panel of the product.



When installing the product on a console or shelf, make sure that the front of the product does not protrude out of the console or shelf.

- Make sure to use a cabinet or shelf suitable to the size of the product.





Otherwise, it may result in a problem with the product or injury.



If the product is installed in a location where the operating conditions vary considerably, a serious quality problem may occur due to the surrounding environment. In this case, install the product only after consulting one of our service engineers about the matter.

Places exposed to microscopic dust, chemicals, too high or low temperature, high humidity, such as airports or stations where the product is continuously used for a long time and so on.

Cleaning Related



Since using a surfactant, which contains a large amount of alcohol, solvent or other strong chemicals, may result in the discoloration or cracking of the product exterior or the panel surface coming off, be sure to use the recommended cleansing agent only.

You can purchase the recommended cleansing agent from a service center.



Before cleaning the product, unplug the power cord.

Otherwise, it may result in electric shock or



When cleaning the product, do not spray water directly over the product parts.

- Make sure that water does not enter the product.
- Otherwise, it may result in fire, electric shock or a problem with the product.

Major Safety Precautions 1-3

Caution



Avoid spraying cleansing agent directly onto the product.

This may result in discoloration or cracking of the exterior of the product or the panel coming off.



When cleaning the product, disconnect the power cord and clean the product with a soft dry cloth.

Avoid using chemicals such as wax, benzene, alcohol, thinner, mosquitorepellent, fragrance, lubrication or cleansing agent when cleaning the product. This may result in the exterior being deformed or the print being removed.



Use a soft, damp cloth with a "monitorexclusive cleansing agent" and wipe the product with it.

If no monitor-exclusive cleansing agent is available, dilute a cleansing agent with water at a ratio of 1:10 before cleaning the product.



Since the exterior of the product is easily scratched, be sure to use a proper cleansing cloth. Use the cleansing cloth with a small amount of water. However, if the cloth is contaminated by alien substances, it may result in scratches to the exterior; therefore shake off any alien substances from the cloth before using it.

Usage Related



Warning



Since a high voltage runs through the product, never disassemble, repair or modify the product

- Otherwise, it may result in fire or electric shock.
- If the product needs to be fixed, contact a service center.



If the product generates a strange noise, a burning smell, or smoke, unplug the power plug immediately and contact a service center.

Otherwise, it may result in electric shock or



If you drop the product or the case is damaged, turn the power off and unplug the power cord. Contact a service center.

Otherwise, it may result in fire or electric shock.



When thunder or lighting occurs, unplug the power cord and under no circumstance touch the antenna cable as this is dangerous.

Otherwise, it may result in electric shock or fire.



When cleaning the product, do not spray water directly over the product parts.

- Make sure that water does not enter the product.
- Otherwise, it may result in fire, electric shock or a problem with the product.



Avoid letting children to hang or climb onto the

Otherwise, it may result in the product falling and this may result in injury or death.



Avoid placing objects such as toys and cookies on top of the product.

If a child hangs over the product to grab an object, the object or the product may fall and this may result in injury or even death.



Avoid dropping an object over the product or cause impact to the product.

Otherwise, it may result in electric shock or





Avoid moving the product by pulling the power cord or antenna cable.

Otherwise, it may result in electric shock, fire or a problem with the product due to damage to the cable.



When a gas leak occurs, do not touch the product or the power plug and ventilate immediately.

- A spark may result in an explosion or fire.
- During a thunder or lighting storm, do not touch the power cord or antenna cable.

Avoid using or placing inflammable spray or objects near the product.

This may result in an explosion or fire.



Avoid lifting up or move the product by holding only the power cord or signal cable.

Otherwise, it may result in electric shock, fire or a problem with the product due to damage to the cable.



Take care not to block the vent by a table cloth or curtain.

Otherwise, it may result in fire due to internal overheating.



Avoid inserting metal objects such as a chopsticks, coins or hairpins, or inflammable objects into the product (the vents, ports, etc).

- If water or an alien substance enters the product, turn the power off, unplug the power cord and contact a service center.
- Otherwise, it may result in a problem with the product, electric shock or fire.



Avoid placing a liquid container such as a vase, flowerpot, beverage, cosmetics or drugs, or a metal object over the product.

- If water or an alien substance enters the product, turn the power off, unplug the power cord and contact a service center.
- Otherwise, it may result in a problem with the product, electric shock or fire.



Caution



Displaying a still image for a long time may create a persistent image or stain on the

If you do not use the product for a long time, use the power-saving mode or set the screensaver to the moving picture mode.



When not using the product for a long time such as leaving your home, unplug the power cord from the wall outlet.

Otherwise, it may cause dust accumulation and result in fire caused by overheating or short circuit or result in an electric shock.



Set the appropriate resolution and frequency for the product.

Otherwise, it may result in eye strain.



Avoid turning the product upside down or move the product holding only the stand.

This may cause the product to fall resulting in damage to the product or injury.

Keep power adaptor away from any other heat



Do not place the adapter on top of another adapter.

Otherwise, it may result in fire.



Otherwise, it may result in fire.

source.



Remove the vinyl cover of the adapter before using the adaptor.

Otherwise, it may result in fire.



Always keep power adaptor in well-ventilated area.

Major Safety Precautions 1-3



Be careful that adaptor should not be in contact with water and therefore not be wet.

This may cause a malfunction, electric shock or fire. Do not use adaptor by the waterside or outside particularly when it rains or snows. Be careful that adaptor should not be wet while cleaning floor with water.



Watching the product from too close a distance continuously may damage your eyesight.



Avoid using a humidifier or cooker near the product.

Otherwise, it may result in electric shock or fire

Since the display panel is hot after using it for a



It is important to give your eyes some rest (5 minutes every hour) when viewing the product screen for long periods of time.

This will alleviate any eye strain.





Take care when adjusting the angle of the product or the height of the stand.

long time, do not touch the product.

- If your hand or finger is caught, you may be injured.
- If the product is tilted excessively, the product may fall and this may result in injury.



Avoid placing a heavy object over the product.

Otherwise, it may result in a problem with the product or injury.

Maintaining the Correct Posture when Using this Product



Maintain the correct posture when using this product.

- · Straighten your back.
- Keep a distance of 45~50 cm from your eyes to the screen. Look down at the screen and face the screen forwards.
- Adjust the angle of the product so that light is not reflected onto the screen.
- Keep your elbow at a right angle and keep your arm level with the back of your hand.
- · Keep your elbow at a right angle.
- Place your heels flat on the ground while keeping your knees at an angle of 90 degrees or higher and maintain the position of your arm so that your arm is below your heart.

1-3 Major Safety Precautions

2 Installing the Product

2-1 Package Contents

- Unpack the product and check if all of the following contents have been included.
 - Store the packaging box in case you need to move the Product at a later stage.



Monitor

CONTENTS				
Installation Manual	Product Warranty	User Manual	'DVI-A to D-Sub' Cable	
	(Not available in all locations)		(Not available in all locations)	
Power Cord	DC-Adapter	Cleaning Cloth	Stand Connector	
Stand				
OPTIONAL PARTS				
DVI Cable				

The cleaning cloth is supplied with black high-glossy models only.

Installing the Product 2-1


Before assembling the product, place the product down on a flat and stable surface so that the screen is facing downwards.



Insert the Stand Connector into the Stand in the direction shown by the figure.



Check if the Stand Connector is firmly connected.



Turn the connecting screw at the bottom of the stand fully so that it is completely fixed.



Place a soft cloth over the table to protect the product and place the product onto the cloth so that the front of the product is facing downwards.



Hold the main body of the product with your hand as shown by the figure.

Push the assembled stand into the main body in the direction of the arrow as shown in the figure.



- Caution

Avoid lifting the product holding only the stand.

Installing the Product 2-2

Before removing the stand, place the product down on a flat and stable surface so that the screen faces downwards.




Place a soft cloth over the table to protect the product and place the product onto the cloth so that the front of the product faces downwards.



Hold the main body of the product with your hand as shown by the figure.

Pull the stand in the direction of the arrow as shown in the figure to separate it.




Turn the connecting screw at the bottom of the stand to separate it.




Take the Stand Connector out of the Stand by pulling it in the direction of the arrow as shown in the figure.

2-3

- The connecting part may differ depending on the product model.
- 1. Connect the product to a PC depending on the video output supported by the PC.
 - When the graphics card provides D-Sub (<Analog>) output
 - · Connect the [DVI IN] port of the product to the [D-Sub] port on your PC using the DVI-A to D-Sub cable.



- When the graphics card provides DVI(<Digital>) output
 - Connect the [DVI IN] port of the product to the DVI port of the PC with the DVI cable.



2. Connect one end of the power cord to the DC-Adapter and plug the other end into a dedicated 220V or 110V wall outlet. (The input voltage is switched automatically.)



When the product is connected to a PC, you can turn the product on and use it.

When both the DVI (<Digital>) and D-Sub (<Analog>) cables are connected, you can select the input signal <Analog/Digital> by pressing the button.

Installing the Product 2-4

2-5 Kensington Lock

A Kensington Lock is an anti-theft device that enables users to lock the product so that they can safely use it in public locations. Since the shape and usage of the locking device may differ depending on the model and the manufacturer, for more information, refer to the User Manual supplied with the locking device. You have to purchase an additional locking device.



Locking the product

- 1. Insert the locking part of the locking device into the hole of the Kensington lock of the product(B) and turn it in the locking direction(A).
- 2. Connect the Kensington lock cable.
- 3. Tie the Kensington lock cable to a desk or heavy object.
- You can purchase the locking device from an electronics store, an online shop, or our service center.

2-5 Installing the Product

3 Using the product

3-1 Setting the Optimal Resolution

If you turn the power on after purchasing the product, a message regarding the optimal resolution setting appears on the screen. Select a language and the optimal resolution.



▲/▼ : You can select a language with these buttons.

MENU: If you press this button, the message disappears.

- The message appears up to 3 times if the resolution has not been set to the optimal resolution.
 - To set the resolution to the optimal resolution
 - When the PC is turned off, connect the product and the PC and turn the power on.
 - Right-click over the Desktop and select 'Properties' from the pop-up menu.
 - In the 'Settings' tab, set the resolution to the optimal resolution.

Using the product 3-1

3-2 Standard Signal Mode Table

The LCD monitor has one optimal resolution for the best visual quality depending on the screen size due to the inherent characteristics of the panel, unlike for a CDT monitor.

Therefore, the visual quality will be degraded if the optimal resolution is not set for the panel size. It is recommended setting the resolution to the optimal resolution of the product.

If the signal from the PC is one of the following standard signal modes, the screen is set automatically. However, if the signal from the PC is not one of the following signal modes, a blank screen may be displayed or only the Power LED may be turned on. Therefore, configure it as follows referring to the User Manual of the graphics card.

3-2

DISPLAY MODE	HORIZONTAL FREQUENCY (KHZ)	VERTICAL FREQUENCY (HZ)	PIXEL CLOCK (MHZ)	SYNC POLARITY (H/V)
IBM, 640 x 350	31.469	70.086	25.175	+/-
IBM, 720 x 400	31.469	70.087	28.322	-/+
VESA, 640 x 480	31.469	59.940	25.175	-/-
MAC, 640 x 480	35.000	66.667	30.240	-/-
VESA, 640 x 480	37.861	72.809	31.500	-/-
VESA, 640 x 480	37.500	75.000	31.500	-/-
VESA, 800 x 600	35.156	56.250	36.000	+/+
VESA, 800 x 600	37.879	60.317	40.000	+/+
VESA, 800 x 600	48.077	72.188	50.000	+/+
VESA, 800 x 600	46.875	75.000	49.500	+/+
MAC, 832 x 624	49.726	74.551	57.284	-/-
VESA, 1024 x 768	48.363	60.004	65.000	-/-
VESA, 1024 x 768	56.476	70.069	75.000	-/-
VESA, 1024 x 768	60.023	75.029	78.750	+/+
VESA, 1152 x 864	67.500	75.000	108.000	+/+
MAC, 1152 x 870	68.681	75.062	100.000	-/-
VESA, 1280 x 800	49.702	59.810	83.500	-/+
VESA, 1280 x 800	62.795	74.934	106.500	-/+
VESA, 1280 x 960	60.000	60.000	108.000	+/+
VESA, 1280 x 1024	63.981	60.020	108.000	+/+
VESA, 1280 x 1024	79.976	75.025	135.000	+/+
VESA, 1440 x 900	55.935	59.887	106.500	-/+
VESA, 1440 x 900	70.635	74.984	136.750	-/+
VESA, 1600 x 1200	75.000	60.000	162.000	+/+
VESA, 1680 x 1050	65.290	59.954	146.250	-/+
VESA, 1920 x 1080	67.500	60.000	148.500	+/+

Horizontal Frequency

The time taken to scan one line from the left-most position to the right-most position on the screen is called the horizontal cycle and the reciprocal of the horizontal cycle is called the horizontal frequency. The horizontal frequency is represented in kHz.


Vertical Frequency

A panel must display the same picture on the screen tens of times every second so that humans can see the picture. This frequency is called the vertical frequency. The vertical frequency is represented in Hz.

Using the product 3-2

3-3 Installing the Device Driver


- If you install the device driver, you can set up the appropriate resolution and frequency for the product. The device driver is included on the CD-ROM supplied with the product. If the supplied drive file is corrupted, please visit a service center or Samsung Electronics website(http://www.samsung.com/), and download the driver.
- 1. Insert the driver installation CD-ROM into the CD-ROM drive.
- 2. Click on "Windows Driver".
- 3. Complete the remaining installation steps according to the instructions displayed on the screen.
- 4. Select the model of your product from the model list.



5. Check if the appropriate resolution and screen refresh rate are displayed in the Control Panel settings. For more information, refer to the document about the Windows operating system.

3-3

Product Operating Buttons



ICON	DESCRIPTION
MENU	Press this button to view the On Screen Display (OSD).
	This button is also used to exit the OSD or to return to a higher-level OSD menu
	* OSD Adjustment Lock
	This function locks the OSD in order to maintain the current settings or to prevent the settings from being changed by another person
	On: If you press and hold the MENU button down for 5 seconds, the OSD Adjustment Lock function is activated.
	Off: If you press and hold the MENU button down for 5 seconds again, the OSD Adjustment Lock function is disabled.
	Even if the OSD Adjustment Lock function is activated, users can adjust the brightness and contrast and can set up the adjustment function assigned to the [
▲/ ▼	Use these buttons to navigate the menu or to adjust a value in the OSD.
	Users can set the Customized Key to one of the following functions. If the user presses the Customized Key [n] after setting it, the configured function will be performed.
	<magicbright> - <magicangle> - <magiceco> - <image size=""/></magiceco></magicangle></magicbright>
	You can set the function of the Customized Key by selecting <setup&reset> -> <customized key=""> in the OSD.</customized></setup&reset>
Φ	Use this button to control the brightness of the screen.
<u>_</u> /•	Use this button to select a function.
	If you press the [[] button when there is no OSD, the input signal (Analog/Digital) is
	switched. When the input signal is switched by pressing [☐/—] button or the product is turned on, a message displaying the selected input signal appears at the top left of the screen.
	■ To select Digital mode, you have to connect the product and the PC with the DVI cable.

Using the product 3-4

ICON	DESCRIPTION
AUTO	Press [AUTO] button to adjust the screen settings automatically.
	This function is only available in Analog mode.
	If the resolution settings are changed in the Display Properties, the AUTO adjustment function is performed.
Ф	Press this button to turn the product on or off
	The buttons on the right of the product are touch-type buttons.
	Touch the buttons lightly with your finger.
	Power LED
	This LED is turned on when the product works normally.
	Solution For more information on the power-saving function, refer to the power saving function in More Information. When not using the product for a long time, unplugging the power cord is recommended to minimize power consumption.

3-4 Using the product

3-5 Using the Screen Adjustment Menu (OSD: On Screen Display)

The Screen Adjustment Menu (OSD: On Screen Display) Structure

TOP MENUS	SUB MENUS				
PICTURE	Brightness	Contrast	Sharpness	MagicBright	MagicAngle
	Coarse	Fine	Response Time		
COLOR COLOR	MagicColor	Red	Green	Blue	Color Tone
	Color Effect	Gamma			
SIZE & POSI-	H-Position	V-Position	Image Size	Menu H-Position	Menu V-Position
0	Reset	Language	MagicEco	LED On/Off	LED Brightness
SETUP&RESET	Off Timer On/Off	Off Timer Setting	Customized Key	Auto Source	PC/AV Mode
	Display Time	Menu Transpar- ency			
INFORMA- TION					

PICTURE



MENU	DESCRIPTION
Brightness	Controls the screen brightness.
	This menu is unavailable when <magicbright> is set to <dynamic contrast=""> mode.</dynamic></magicbright>
Contrast	Controls the contrast of the pictures displayed on the screen
	This menu is unavailable when <magicbright> is set to <dynamic contrast=""> mode.</dynamic></magicbright>
	This menu is unavailable when <magiccolor> is set to <full> mode or <intelligent> mode.</intelligent></full></magiccolor>
Sharpness	Controls the clarity of details of pictures displayed on the screen
	This menu is unavailable when <magicbright> is set to <dynamic contrast=""> mode.</dynamic></magicbright>
	This menu is unavailable when <magiccolor> is set to <full> mode or <intelligent> mode.</intelligent></full></magiccolor>

Using the product 3-5

MENU	DESCRIPTION
MagicBright	Provides preset picture settings optimized for various user environments such as editing a document, surfing the Internet, playing games, watching sports or movies and so on. • <custom> If the preset picture modes are not sufficient, users can configure the Contrast</custom>
MagicAngle	This feature allows you to see optimal screen quality according to your viewing position. When viewing the screen at an angle from below, above or the side of the monitor, by setting the appropriate mode for each position you can obtain a similar picture quality as viewing the screen directly from the front. Set to <off> when viewing directly in front of the screen. • <off> Select when viewing from the front position. • <lean back="" mode1=""> Select when viewing from a slightly lower position. • <standing mode=""> Select when viewing from the lower position. • <side mode=""> Select when viewing from the upper position. • <side mode=""> Select when viewing from the left or right position. • <custom> -When <custom> is selected, settings for <lean 1="" back="" mode=""> is applied by default. Users can set suitable picture quality as needed. • This menu is unavailable when <magicbright> is set to <dynamic contrast=""> mode.</dynamic></magicbright></lean></custom></custom></side></side></standing></lean></off></off>
	This menu is unavailable when <magiccolor> or <color effect=""> is set.</color></magiccolor>

MENU	DESCRIPTION
Coarse	Removes vertical noise lines (line pattern) from the screen.
	The location of the screen may be changed after the adjustment. In this case, move the screen so that the screen is displayed at the center of the display panel using the <h-position> menu.</h-position>
	This function is only available in Analog mode.
Fine	Removes horizontal noise lines (line pattern) from the screen.
	If you cannot remove the noise completely with the <fine> function, adjust the <coarse> and then use the <fine> function again.</fine></coarse></fine>
	This function is only available in Analog mode.
Response Time	Accelerates the response time of the LCD panel faster than the original response time so that moving pictures appear sharper and more natural.
	• <normal></normal>
	<faster></faster>
	<pre>• <fastest></fastest></pre>
	■ It is recommended setting the <normal> or <faster> when not viewing a movie.</faster></normal>

COLOR




Using the product 3-5

MENU	DESCRIPTION
MagicColor	Expresses natural colors more clearly without changing the picture quality using proprietary digital picture quality improvement technology developed by Samsung Electronics.
	<off> - Turns the MagicColor function off.</off>
	• <demo> - You can compare the pictures processed by MagicColor with the original pictures.</demo>
	Full> - Provides a clearer picture including areas corresponding to skin color.
	Intelligent> - Improves the chroma of pictures except for areas corresponding to skin color.
Red	You can adjust the red color value of pictures according to your preference.
	This menu is unavailable when <magiccolor> is set to <full> mode or <intelligent> mode.</intelligent></full></magiccolor>
Green	You can adjust the green color value of pictures according to your preference.
	This menu is unavailable when <magiccolor> is set to <full> mode or <intelligent> mode.</intelligent></full></magiccolor>
Blue	You can adjust the blue color value of pictures according to your preference.
	This menu is unavailable when <magiccolor> is set to <full> mode or <intelligent> mode.</intelligent></full></magiccolor>
Color Tone	You can set the color temperature according to your preference.
	<cool> - Sets the color temperature of the screen to a cooler color.</cool>
	<normal> - Sets the color temperature of the screen to the standard color temperature.</normal>
	< Warm> - Sets the color temperature of the screen to a warmer color.
	Custom> - Select this menu to set the color temperature manually.
	If you do not like the preset color temperatures, you can manually adjust the colors of <color effect="">.</color>
	This menu is unavailable when <magiccolor> is set to <full> mode or <intelligent> mode.</intelligent></full></magiccolor>
Color Effect	You can change the overall atmosphere by changing the color of pictures.
	This menu is unavailable when <magiccolor> is set to <full> mode or <intelligent> mode.</intelligent></full></magiccolor>
	<off> - Turns the <color effect=""> function off.</color></off>
	<aqua> - Displays pictures in aqua mono color.</aqua>
	<sepia> - Displays pictures in sepia mono color.</sepia>
Gamma	Using this menu, you can change the intensity of the colors of medium brightness.
	• <mode1> - <mode2> - <mode3></mode3></mode2></mode1>

(This is unavailable when MagicBright is set to <Dynamic Contrast> mode.)

■ SIZE & POSITION



MENU	DESCRIPTION
H-Position	Moves the position of the display area on the screen horizontally.
	 This function is only available in Analog mode.
	 When TV signal is input in AV mode ,select <screen fit="">to adjust horizontal position in 0-6 levels.</screen>
V-Position	Moves the position of the display area on the screen vertically.
	 This function is only available in Analog mode.
	 When TV signal is input in AV mode ,select <screen fit="">to adjust vertical position in 0-6 levels.</screen>
Image Size	PC signals
	- <auto> - The picture is displayed at the aspect ratio of the input signal.</auto>
	 <
	A signal not in the standard mode table is not supported.
	 If the resolution is set to the optimal resolution, the aspect ratio does not change whether the <image size=""/> is set to <auto> or <wide>.</wide></auto>
	AV signals
	• <4: 3> - Displays pictures at the 4:3 aspect ratio.
	<16 : 9> - Displays pictures at the 16:9 aspect ratio.
	 <screen fit=""> - If a 720P, 1080i or 1080P signal is input in DVI input mode, the picture is displayed as is without truncation.</screen>
	This can only be set when the external input is connected through DVI and <pc av="" mode=""> is set to <av>.</av></pc>
Menu H-Position	You can adjust the horizontal position of the OSD.
Menu V-Position	You can adjust the vertical position of the OSD.

SETUP&RESET



Using the product 3-5

MENU	DESCRIPTION
Reset	Use this function to restore the visual quality and color settings to the factory defaults.
	• <no> - <yes></yes></no>
Language	Select a language for the OSD.
	 English, Deutsch, Español, Français, Italiano, Svenska, Русский, Português, Türkçe
	The selected language is only applied to the product OSD. This setting does not affect the other functions of the PC.
MagicEco	This function provides user a low power mode which is realized by lowering the current of the display panel.
	<100%> When <100%> is selected, the power consumption is 100% of default setting.
	• <75%> When <75%> is selected, the power consumption is about 75% of default setting.
	• <50%> When <50%> is selected, the power consumption is about 50% of default setting.
	• <power off="" saving=""> When <power off="" saving=""> is selected, the function is turned Off.</power></power>
	This menu is unavailable when <magicbright> is set to <dynamic contrast=""> mode.</dynamic></magicbright>
LED On/Off	Turns the Menu button LED on or off.
	<off> - Turns the Power button LED lamp off.</off>
	• <on> - Turns the Power button LED lamp on.</on>
LED Brightness	Adjusts the brightness of the Menu button LED in levels.
Off Timer On/Off	You can turn the Off Timer on or off.
	• <off> - <on></on></off>
Off Timer Setting	Turns the power off automatically when the configured time is reached.
Customized Key	You can set the function of the Customized Key to one of the following.
	<magicbright> - <magicangle> - <magiceco> - <image size=""/></magiceco></magicangle></magicbright>
Auto Source	- <auto> - The monitor automatically selects an input signal.</auto>
	<manual> - Users have to manually select an input signal.</manual>
PC/AV Mode	Set to PC when connected to a PC.
	Set to AV when connected to an AV device.
	This function does not support Analog mode.
Display Time	The OSD automatically disappears if no action is taken by the user.
	You can determine the time to wait before the OSD is hidden.
	• <5 sec> - <10 sec> - <20 sec> - <200 sec>
Menu Transparency	You can select the transparency of the OSD.
	• <off> - <on></on></off>

3-5 Using the product

INFORMATION



MENU	DESCRIPTION	
INFORMATION	Shows the frequency and resolution set on the PC.	

Using the product 3-5

4 Installing the Software

4-1 Natural Color

What is Natural Color?

This software works only for Samsung products and enables adjusting the displayed colors on the product and matches the colors on the product with the colors of the printed pictures. For more information, refer to the online help of the software (F1).

The Natural Color is provided online. You can download it from the website below and install;

http://www.samsung.com/us/consumer/learningresources/monitor/naturalcolorexpert/pop_download.html

4-1 Installing the Software

What is MagicTune?



MagicTune is a software program that helps with monitor adjustments by providing comprehensive descriptions of monitor functions and easy-to-understand guidelines.

Users can adjust the product with the mouse and the keyboard without using the operating buttons of the product.

Installing the Software

- 1. Insert the installation CD into the CD-ROM drive.
- 2. Select the MagicTune setup program.
 - If the pop-up screen for the software installation does not appear on the main screen, find and double-click the MagicTune setup file on the CD-ROM.
- 3. Select the installation language and click [Next].
- 4. Complete the remaining software installation steps according to the instructions displayed on the screen.
- The software may not work properly if you do not restart the computer after the installation.
 - The MagicTune icon may not appear depending on the computer system and the product specifications.
 - If the shortcut icon does not appear, press the F5 key.

Restrictions and Problems with the Installation (MagicTune™)

The installation of MagicTune™may be affected by the graphics card, motherboard and the networking environment.

System Requirements

os

- Windows 2000
- · Windows XP Home Edition
- · Windows XP Professional
- Windows Vista 32Bit
- · Windows 7 32Bit
- For MagicTune™, Windows 2000 or later is recommended.

Hardware

- · At least 32MB of memory
- · At least 60MB of free space on the hard disk drive
- For more information, refer to the website.

Removing the Software

You can only remove MagicTune™through [Add or Remove Programs] in Windows.

To remove MagicTune $\ensuremath{^{\text{TM}}}$, complete the following steps.

1. Click [Start] select [Settings], and select [Control Panel] from the menu. For Windows XP, click [Start], and select [Control Panel] from the menu.

Installing the Software 4-2

- 2. Double-click the [Add or Remove Programs] icon in the Control Panel.
- 3. In the [Add/Remove] window, find and select MagicTune™so that it is highlighted.
- 4. Click [Change or Remove Programs] to remove the software.
- **5.** Select [Yes] to start removing MagicTune™.
- 6. Wait until a message box appears informing you that the software has been removed completely.
- Solution For technical support, the FAQ (frequently asked questions) or information about the software upgrade for MagicTune™, please visit our website.

4-2 Installing the Software

What is MultiScreen?



MultiScreen enables users to use the monitor by partitioning multiple sections.

Installing the Software

- 1. Insert the installation CD into the CD-ROM drive.
- 2. Select the MultiScreen setup program.
 - If the pop-up screen for the software installation does not appear on the main screen, find and double-click the MultiScreen setup file on the CD-ROM.
- 3. When the Installation Wizard appears, click [Next].
- 4. Complete the remaining software installation steps according to the instructions displayed on the screen.
 - The software may not work properly if you do not restart the computer after the installation.
 - · The MultiScreen icon may not appear depending on the computer system and the product specifications.
 - If the shortcut icon does not appear, press the F5 key.

Restrictions and Problems with the Installation (MultiScreen)

The MultiScreen installation may be affected by the graphics card, motherboard and the networking environment.

Operating System

os

- Windows 2000
- Windows XP Home Edition
- Windows XP Professional
- · Windows Vista 32Bit
- · Windows 7 32Bit
- For MultiScreen, the operating systems Windows 2000 or later is recommended.

Hardware

- · At least 32MB of memory
- · At least 60MB of free space on the hard disk drive

Removing the Software

Click [Start], select [Settings]/[Control Panel], and then double-click [Add or Remove Programs].

Select MultiScreen from the program list and click the [Add/Delete] button.

Installing the Software 4-3

5 Troubleshooting

5-1 Monitor Self-Diagnosis

- You can check if the product is working properly using the Self-Diagnosis function.
 - If a blank screen is displayed and the Power LED blinks even if the product and the PC are properly connected, perform the self-diagnosis function according to the procedures below.
- 1. Turn the product and the PC off.
- 2. Separate the signal cable from the product .
- 3. Turn the product on.
- **4.** If the product is working properly, the <Check Signal Cable> message appears.

 In this case, if a blank screen is displayed again, make sure that there is no problem with the PC and the connection. The product is working properly.

5-1 Troubleshooting

Please check the following before requesting After-Sales service. If the problem continues, please contact your nearest Samsung Electronics Service Center.

A BLANK SCREEN APPEARS / I CANNOT TURN THE PRODUCT ON			
Is the power cord connected properly?	Check the connection status of the power cord.		
Is the <check cable="" signal=""> message displayed on the</check>	Check the cable connecting the PC and the product.		
screen?	If the message appears on the screen even if the cable is properly connected, recheck the input signal by pressing the DD button of the product.		
Is the <not mode="" optimum=""> message displayed on the screen?</not>	This occurs when the signal from the graphics card exceeds the maximum resolution or the maximum frequency of the product.		
	In this case, set up the appropriate resolution and the frequency for the product.		
Is a blank screen displayed and does the power LED blink at	This occurs when the power saving function is running.		
a 1 second interval?	If you click the mouse or press any key, the screen will be turned on.		
Did you connect with a DVI cable?	If you connect the DVI cable when the PC has booted up or if you reconnect the DVI cable after disconnecting the cable while using a PC, the screen may not be displayed because some graphics cards do not output the video signal.		
	In this case, reboot the PC while the DVI cable is connected.		
THE IMAGE IS TOO L	IGHT OR TOO DARK.		
Adjust the <brightness> and <contrast>.</contrast></brightness>			
(Refer to the <brightness>, <contrast>)</contrast></brightness>			
The display brightness can differ according to the mode set for <magicangle>.</magicangle>			
If <magicbright> is set to <dynamic contrast="">, the display bright</dynamic></magicbright>	htness can differ according to the input signal.		
THE ON SCREEN ADJUSTMENT I	MENU (OSD) DOES NOT APPEAR.		
Did you cancel the screen adjustment?	Check if the OSD Adjustment Lock function is set to Off.		
THE COLOR IS WEIRD / THE PICTURE	IS DISPLAYED IN BLACK AND WHITE		
Is the entire screen displayed in the same color as if viewing the screen through a cellophane paper?	Check the cable connection to the computer. Reinsert the graphics card into the computer completely.		
	Check if the <color effect=""> is set to <off>.</off></color>		
Is the graphics card configured correctly?	Set up the graphics card referring to the user manual.		
THE DISPLAY AREA SUDDENLY MOVES TO AN EDGE OR TO THE CENTER.			
Did you change the graphics card or the driver?	Please press the [AUTO] button to run the auto adjustment function.		
	Set the resolution and the frequency to the appropriate values		
Did you change the resolution and frequency appropriate to the product?	in the graphics card		

Troubleshooting 5-2

THE PICTURES ARE OUT-OF-FOCUS.				
Did you change the resolution and the frequency appropriate to the product?	Set the resolution and the frequency to the appropriate values in the graphics card refer to the (Standard Signal Mode Table)			
THE COLOR IS DISPLAYED IN 16 BIT (16 COLORS). THE COLOR HAS BEEN CHANGED AFTER CHANGING THE GRAPHICS CARD.				
Did you install the device driver for the product?	Windows XP : Set the color again by selecting Control Panel → Appearance and Themes → Display → Settings.			
	Windows ME/2000 : Set the color again by selecting Control Panel \rightarrow Display \rightarrow Settings.			
	Windows Vista : Change the color settings by selecting Control Panel \rightarrow Appearance and Personalization \rightarrow Personalization \rightarrow Display settings.			
	Windows 7 : Change the color settings by selecting Control Panel → Appearance and Personalization → Display → Adjust resolution → Advanced settings → Monitor.			
	(For more information, refer to the Windows user manual for the computer.)			
Is the graphics card configured correctly?	Configure the color again in accordance with the new graphics card driver.			
WHEN I CONNECT THE MONITOR, THE 'UNKNOWN MONITOR, PLUG&PLAY (VESA DDC) MONITOR FOUND' MESSAGE IS DISPLAYED.				
Did you install the device driver for the product?	Install the device driver referring to the descriptions about the driver installation.			
Check if all the Plug&Play (VESA DDC) functions are supported referring to the User Manual of the graphics card.	Install the device driver referring to the descriptions about the driver installation.			
WHEN I LOOK AT THE EXTERIOR EDGES OF THE	PRODUCT, SMALL ALIEN SUBSTANCES APPEAR ON IT.			
Since this product is designed so that the color has a soft appearance by coating it with a transparent material over the black edges, such things may be seen. This is not a defect of the product.				
A "BEEP. BEEP" SOUND IS HEA	RD WHEN BOOTING THE COMPUTER.			

A "BEEP, BEEP" SOUND IS HEARD WHEN BOOTING THE COMPUTER.

If the beep sound is generated 3 or more times when booting up the computer, please request service for the computer.

5-2 Troubleshooting

FAQ!	PLEASE TRY THE FOLLOWING!
How can I change the frequency (refresh rate) of the video signal?	You have to change the frequency of the graphics card. Windows XP: Change the frequency by selecting Control Panel → Appearance and Themes → Display → Settings → Advanced → Monitor, and then change the refresh rate under Monitor Settings. Windows ME/2000: Change the frequency by selecting Control Panel → Display → Settings → Advanced → Monitor, and then change the refresh rate under Monitor Settings. Windows Vista: Change the frequency by selecting Control Panel → Appearance and Personalization → Personalization → Display settings → Advanced settings → Monitor, and then change the refresh rate under Monitor Settings. Windows 7: Change the frequency by selecting Control Panel → Appearance and Personalization → Display → Adjust resolution → Advanced settings → Monitor, and then change the refresh rate under Monitor Settings. (For more information, refer to the User Manual of the com-
How can I change the resolution?	puter or the graphics card.) Windows XP : Change the resolution by selecting Control Panel → Appearance and Themes → Display → Settings. Windows ME/2000 : Change the resolution by selecting Con-
	trol Panel → Display → Settings. Windows Vista: Change the resolution by selecting Control Panel → Appearance and Personalization → Personalization → Display settings. Windows 7: Change the resolution by selecting Control Panel → Appearance and Personalization → Display → Adjust reso-
	lution. (For more information, refer to the User Manual of the computer or the graphics card.)
How can I use the power saving function?	Windows XP : Configure it by selecting Control Panel → Appearance and Themes → Display → Screen Saver Setting or configure it in the BIOS Setup of the computer.
	Windows ME/2000 : Configure it by selecting Control Panel → Display → Screen Saver Setting or Configure it in the BIOS Setup of the computer.
	Windows Vista : Change settings by selecting Control Panel → Appearance and Personalization → Personalization → Screen Saver. You can also use the BIOS SETUP menu on the PC.
	Windows 7 : Change settings by selecting Control Panel \rightarrow Appearance and Personalization \rightarrow Personalization \rightarrow Screen Saver. You can also use the BIOS SETUP menu on the PC.
	(For more information, refer to the Windows user manual for the computer.)

Troubleshooting 5-3

6 More Information

6-1 Specifications

MODEL NAME		XL2270	
	Size	21.5 inches (54 cm)	
LCD Panel	Display area	476.64 mm (H) x 268.11 mm (V)	
	Pixel Pitch	0.24825 mm (H) x 0.24825 mm (V)	
Synchroniza-	Horizontal	30 ~ 81 kHz	
tion	Vertical	56 ~ 75 Hz	
Display Color		16.7 M	
December 2	Optimum resolution	1920 x 1080 @ 60 Hz	
Resolution	Maximum resolution	1920 x 1080 @ 60 Hz	
		DVI(Digital Visual Interface)- I	
Innut Cianal Ta	a manima ata al	0.7 Vp-p ±5 %	
Input Signal, Te	erminated	Separate H/V sync, Composite, SOG	
		TTL level (V high ≥ 2.0 V, V low ≤ 0.8 V)	
Maximum Pixel	Clock	164MHz (Analog,Digital)	
		This product supports 100-240 V.Since the standard voltage may differ from	
Power Supply		country to country, please check the label on the back of the product. (Less than 30Ap-p at AC 120V or 50Ap-p at AC 220V)	
Signal Cable		'DVI-A to D-Sub' cable, Detachable	
		'DVI-D to DVI-D' cable, Detachable	
· ·	xHxD) / Weight (Simple	536.3 x 345.2 x 49.6 mm (21.1 x 13.6 x 2.0 inches) (Without Stand)	
stand)		536.3 x 403 x 189.5 mm (21.1 x 15.9 x 7.5 inches) (With Stand) / 3.6 kg (7.9 lbs)	
	Operating	Temperature : 50°F ~ 104°F (10°C ~ 40°C)	
Environmen-	Operating	Humidity :10 % ~ 80 %, non-condensing	
tal consider- ations	01	Temperature : -4°F ~ 113°F (-20°C ~ 45°C)	
7.12	Storage	Humidity: 5 % ~ 95 %, non-condensing	
Tilt		-2° ~18°(±2°)	

- Design and specifications are subject to change without prior notice.
- Class B (Information Communication equipment for residential use)

 This device is registered for EMC requirements for home use (Class B). It can be used in all areas.

 (Class B equipment emits less electromagnetic waves than Class A equipment.)

6-1 More Information

6-2 Power Saving Function

This monitor has a built-in power management system called PowerSaver. This system saves energy by switching your monitor to low-power mode when it has not been used for a certain amount of time. The monitor automatically returns to normal operation when you press a key on the keyboard. For energy conservation, turn your monitor OFF when it is not needed, or when leaving it unattended for long periods. The PowerSaver system operates with a VESA DPM compliant video card installed in your computer. Use the software utility installed on your computer to set up this feature.

STATE	NORMAL OPERATION	POWER SAVING MODE	POWER OFF
Power Indicator	On	Blinking	Off
Power Consumption	22 watts	1 watts	0.3 watts

More Information 6-2

If you have any questions or comments relating to Samsung products, please contact the SAMSUNG customer care center.

NORTH AMERICA					
U.S.A	1-800-SAMSUNG(726-7864) http://www.samsung.com				
CANADA	1-800-SAMSUNG(726-7864)	http://www.samsung.com			
MEXICO	01-800-SAMSUNG(726-7864)	http://www.samsung.com			
	LATIN AMERICA				
ARGENTINA	0800-333-3733	http://www.samsung.com			
BRAZIL	0800-124-421 4004-0000	http://www.samsung.com			
CHILE	800-SAMSUNG(726-7864)	http://www.samsung.com			
COLOMBIA	01-8000112112	http://www.samsung.com			
COSTA RICA	0-800-507-7267	http://www.samsung.com			
ECUADOR	1-800-10-7267	http://www.samsung.com			
EL SALVADOR	800-6225	http://www.samsung.com			
GUATEMALA	1-800-299-0013	http://www.samsung.com			
HONDURAS	800-7919267	http://www.samsung.com			
JAMAICA	1-800-234-7267	http://www.samsung.com			
NICARAGUA	00-1800-5077267	http://www.samsung.com			
PANAMA	800-7267	http://www.samsung.com			
PUERTO RICO	1-800-682-3180	http://www.samsung.com			
REP. DOMINICA	1-800-751-2676	http://www.samsung.com			
TRINIDAD & TOBAGO	1-800-SAMSUNG(726-7864)	http://www.samsung.com			
VENEZUELA	0-800-100-5303	http://www.samsung.com			
	EUROPE				
AUSTRIA	0810 - SAMSUNG(7267864,€ 0.07/min)	http://www.samsung.com			
BELGIUM	02-201-24-18	http://www.samsung.com/be (Dutch)			
		http://www.samsung.com/be_fr (French)			
CZECH	800 - SAMSUNG (800-726786)	http://www.samsung.com			
	Distributor pro Českou republiku: Samsung Zrt., česká organizační složka, Oasis Florenc, Sokolovská394/17, 180 00, Praha 8				
DENMARK	70 70 19 70	http://www.samsung.com			
EIRE	0818 717100	http://www.samsung.com			
ESTONIA	800-7267	http://www.samsung.com			
FINLAND	030 - 6227 515	http://www.samsung.com			
FRANCE	01 48 63 00 00	http://www.samsung.com			

6-3 More Information

	EUROPE				
GERMANY	01805 - SAMSUNG (726-7864,€ 0,14/ Min)	http://www.samsung.com			
HUNGARY	06-80-SAMSUNG(726-7864) http://www.samsung.com				
ITALIA	800-SAMSUNG(726-7864)	http://www.samsung.com			
LATVIA	8000-7267	http://www.samsung.com			
LITHUANIA	8-800-77777	http://www.samsung.com			
LUXEMBURG	261 03 710	http://www.samsung.com			
NETHERLANDS	0900 - SAMSUNG (0900-7267864) (€ 0,10/Min)	http://www.samsung.com			
NORWAY	815-56 480	http://www.samsung.com			
POLAND	0 801 1SAMSUNG (172678) 022 - 607 - 93 - 33	http://www.samsung.com			
PORTUGAL	80820 - SAMSUNG (726-7864)	http://www.samsung.com			
SLOVAKIA	0800-SAMSUNG(726-7864)	http://www.samsung.com			
SPAIN	902 - 1 - SAMSUNG (902 172 678)	http://www.samsung.com			
SWEDEN	0771 726 7864 (SAMSUNG)	http://www.samsung.com			
SWITZERLAND	0848-SAMSUNG(7267864, CHF 0.08/ min)	http://www.samsung.com/ch http://www.samsung.com/ch_fr (French)			
U.K	0845 SAMSUNG (7267864)	http://www.samsung.com			
CIS					
ARMENIA	0-800-05-555				
AZERBAIJAN	088-55-55-555				
BELARUS	810-800-500-55-500				
GEORGIA	8-800-555-555				
KAZAKHSTAN	8-10-800-500-55-500				
KYRGYZSTAN	00-800-500-55-500	http://www.samsung.com			
MOLDOVA	00-800-500-55-500				
RUSSIA	8-800-555-55-55	http://www.samsung.com			
TADJIKISTAN	8-10-800-500-55-500	http://www.samsung.com			
UKRAINE	0-800-502-000	http://www.samsung.com/ua			
		http://www.samsung.com/ua_ru			
UZBEKISTAN	8-10-800-500-55-500	http://www.samsung.com			
OZDENISTAN	ASIA PACIFIC				
OZBERIGTAN	ASIA PACIFIC				
AUSTRALIA	ASIA PACIFIC 1300 362 603	http://www.samsung.com			
		http://www.samsung.com http://www.samsung.com			
AUSTRALIA	1300 362 603				

More Information 6-3

ASIA PACIFIC				
INDIA	3030 8282 1800 110011 1800 3000 8282 1800 266 8282	http://www.samsung.com		
INDONESIA	0800-112-8888 021-5699-7777	http://www.samsung.com		
JAPAN	0120-327-527	http://www.samsung.com		
MALAYSIA	1800-88-9999	http://www.samsung.com		
NEW ZEALAND	0800 SAMSUNG (0800 726 786)	http://www.samsung.com		
PHILIPPINES	1-800-10-SAMSUNG(726-7864) 1-800-3-SAMSUNG(726-7864) 1-800-8-SAMSUNG(726-7864) 02-5805777	http://www.samsung.com		
SINGAPORE	1800-SAMSUNG(726-7864)	http://www.samsung.com		
TAIWAN	0800-329-999	http://www.samsung.com		
THAILAND	1800-29-3232 02-689-3232	http://www.samsung.com		
VIETNAM	1 800 588 889	http://www.samsung.com		
MIDDLE EAST & AFRICA				
BAHRAIN	8000-4726			
JORDAN	800-22273			
SOUTH AFRICA	0860-SAMSUNG(726-7864)	http://www.samsung.com		
TURKEY	444 77 11	http://www.samsung.com		
U.A.E	800-SAMSUNG(726-7864)	http://www.samsung.com		

6-3 More Information

6-4 Correct Disposal of This Product (Waste Electrical & Electronic Equipment) - Europe only



(Applicable in the European Union and other European countries with separate collection systems)

This marking on the product, accessories or literature indicates that the product and its electronic accessories (e.g. charger, headset, USB cable) should not be disposed of with other household waste at the end of their working life. To prevent possible harm to the environment or human health from uncontrolled waste disposal, please separate these items from other types of waste and recycle them responsibly to promote the sustainable reuse of material resources.

Household users should contact either the retailer where they purchased this product, or their local government office, for details of where and how they can take these items for environmentally safe recycling.

Business users should contact their supplier and check the terms and conditions of the purchase contract. This product and its electronic accessories should not be mixed with other commercial wastes for disposal.

More Information 6-4